

GM

automotive videoscope



Product Feature

1 4.3 inch HD display touch screen



Resolution 800*480

2 Modular design allows for change probes quickly



3 360° damping bending with wear-resistant tungsten braided insertion cable



4 HD 1,000,000 camera pixel module



5 Long working hours



26650 battery

6 Ergonomic design for easy operation and portability



280mm

- Confirm
- Return/Menu Key
- Up
- Down
- Picture enlargement
- Light adjustment
- Playback
- Video

Technical parameters

Category	Specification	GM	
Camera	Camera diameter	3.9mm	6.0mm
	Pixels	720P	
	Material	Stainless steel	
	Length of camera	15mm	
	DOF	10-100mm	15mm-infinity
	LED illumination	> 15,000LUX	> 25,000LUX
	Light type	LED	
Insertion part	Articulation part	4-way	
	Insertion cable	Tungsten braided	
	Insertion cable length	1.5m/3m	
	Joystick control	Built-in damping	
	Articulation control	Manual	
	Battery replacement method	Battery swappable	
	Structural features	Monitor/Probe interchangeable	
Display module	Size	4.3 inch	
	Resolution	800*480	
	Interface	Charge and read data	
	TF card	32G SD card/TF card	
	WIFI	WIFI optional	
	Temperature indicator	High temperature alarm	
	Menu operation	Button/Touch screen	
Software operation	Software settings	Time/Multiple Languages/Energy Saving/Sound/Picture enlargement/SD card Upgrade etc.	
	Language type	Chinese/English/French/German/Japanese/Spanish/Italian/Russian/Korean/Turkish	
Others	Power supply	5V 2A	
	Battery	26650 5000MAH	
	Working hours	4 hours	
	Operating temperature	Controller-10°~50°C	
	Weight	0.75KG	
	Package	Waterproof tool box	
	Waterproof	Controller, IP64/Insertion cable, IP67	
	Drop rating	1M	
	Functional characteristics	White balance/Contrast/Tone/Exposure/Selection/Gain Scale/Watermark/WIFI	

DISTRAME

Parc du Grand Troyes - Quartier Europe Centrale, 40 rue de Vienne - 10300 SAINTE-SAVINE
Tél. : 03 25 71 25 83 - infos@distrame.fr - www.distrame.fr