



## SNYPER-LTE+ (EU)

4G/LTE, 3G/UMTS & 2G/GSM Network Signal Analyser



### General Description

The SNYPER-LTE+ (EU) is a high performance, multi-language network signal analyser dedicated to surveying the 4G/LTE(EU), 3G/UMTS & 2G/GSM European networks.\*


It incorporates a number of important features and can perform four types of survey: 4G/LTE, 3G/UMTS, 2G/GSM and a combined 4G/3G/2G survey. The combined 4G/3G/2G survey will provide multiple results from each network operator, in one single survey.

The powerful SNYPER summary page displays percentage thresholds to determine the most suitable mobile network operator available and the performance of a “preferred” MNO can be evaluated against the other networks.

The SNYPER can also be used to help establish optimum antenna placement and perform local site surveys.


\*SNYPER-LTE+ (EU) does not require a SIM in order to function.

### Features



### Featured Applications

- » Enhanced cellular surveying of new and existing installations on 4G, 3G and 2G networks
- » Establish most suitable operator for application
- » Evaluate your “preferred” MNO’s performance
- » Determine optimum antenna placement
- » Results are reported in CSV & graphical HTML format





## SNYPER-LTE+ (EU)

4G/LTE, 3G/UMTS & 2G/GSM Network Signal Analyser

### General Features

- » 2 Supported Bands GSM | GPRS:  
900/1800MHz
- » 2 Supported Bands UMTS/HSPA+:  
900/2100MHz
- » 5 Supported Bands LTE:  
800/900/1800/2100/2600MHz
- » Blue antenna for 700MHz to 2300 MHz
- » Silver/Grey Antenna for 2600MHz
- » Large easy to read LCD display
- » No SIM required for operation
- » Logical menus and operation
- » Long life rechargeable battery
- » USB battery charger included
- » USB car charger included
- » Rugged and durable construction
- » Supplied in a hard carry case
- » Multiple language support  
(English/French/German/Italian/Spanish)

### Interfaces

- » 1 x USB 2.0 FS(12 Mbits/s) for PC interface and for battery charging
- » 1 x SMA female cellular antenna connector
- » Red LED charging indicator
- » Display: 2.4" Diagonal QVGA 240 x 320 RGB TFT with LED backlight
- » Display: 80 degree viewing angle
- » Display Brightness: 500md/m2

### Power Supply

- » Mains Input: 100-240V 50/60Hz
- » Multi-region Heads: UK / EU /US / AU
- » Charger O/P: 5V DC 2000mA

### Approvals and Compliance

- » CE

### Environmental

- » Dimensions  
SNYPER: 141mm x 76mm x 36mm  
Antenna: 78mm x 11mm
- » Weight  
Without antenna: 200 grams  
With supplied antenna: 207 grams
- » Operating Temperature Range: -10 to +50 deg C
- » Storage Temperature Range: -20 to +50 deg C
- » Operating Humidity Range: 20 to 85% RH Non-condensing
- » Battery: Lithium Ion 3.7V, 2000mAh
- » Life: 48 hours based on 20 surveys /day at room temperature with auto power off enabled
- » Warm up time: 2s

### Reporting

#### HTML Reporting

- » Graphical display ordered by signal strength
- » Listing of advanced cellular parameters
- » Complete summary breakdown for all recorded cells
- » Recorded survey date and time
- » Integrated mapping portal enabled (registration required)

#### CSV Reporting

- » Complete survey breakdown for each recorded cell
- » Listing of advanced cellular parameters